

A

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventor: **Rory Matthew Johnson**

For: **A BOOT FOR A CONSTANT VELOCITY UNIVERSAL JOINT**

are enclosed the following:

- ☒ FOUR (4) sheets of informal drawings.
- ☒ An Assignment Cover Sheet for Recordal of Document of the invention to GKN Automotive, Inc.
- ☒ An Assignment of the invention to GKN Automotive, Inc.
- ☒ A Declaration for Patent Application pursuant to C.F.R. 1.63 and 1.68.
- ☐ Form PTO-1449 (Modified) with attachments.

04/30/99 PTO
161/03/09
04/30/99

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R., 1.10 on the date indicated below and is addressed to Assistant Commissioner for Patents, Washington, D.C. 20231. "Express Mail" mailing label No. EE445922734US, on

April 30, 1999
(Date of Deposit)

Mick A. Nylander

M.A. Nylander
(Signature)

The filing fee has been calculated as shown below:

For:	(Col.1) No. Filed	(Col.2) No. Extra	Small Entity Rate Fee	Other Than A Small Entity Rate Fee
Basic Fee			\$395	\$790
Total Claims	- 20 x 0	x 11 =	x 22 =	
Indep. Claims	- 3 x		x 41 = 1	x 82 =
Multiple Dependent Claims Presented		+135 =		
Assignment Recordal Fee				\$40
			TOTAL \$830.00	

- ☒ Please find enclosed my check in the amount of \$830.00 representing the filing fee for the patent application and \$40.00 to cover the filing fee associated with the filing of the Assignment Recordal Fee.
- ☒ The Commissioner is hereby authorized to charge any underpayment or deficiency in payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 07-1360. A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ Any filing fee associated with the filing of the assignment of the recordal fee under 37 CFR 1.21(h).

Respectfully submitted,

GKN AUTOMOTIVE, INC.

Date of Deposit: April 30, 1999

By:

M.A. Nylander
Mick A. Nylander
Registration No. 37,200
Attorney of Record
3300 University Drive
Auburn Hills, Michigan 48326
(248) 377-1290

04/30/99 PTO

04/30/99 PTO

A BOOT FOR A CONSTANT VELOCITY UNIVERSAL JOINT

Technical Field

5 This invention relates to a boot for a universal joint and more specifically to a rolling diaphragm boot for a constant velocity universal joint.

Background Art

Constant velocity universal joints are sometimes used in vehicles for
coupling the transmission and its corresponding propeller shaft. In four-wheel drive
10 vehicles, constant velocity universal joints are utilized to couple the transfer case to
the front and rear propeller shafts extending therefrom to corresponding front and
rear drive axles. A constant velocity universal joint used in these applications
includes a boot which is crimped into a larger boot-can connector, which in turn is
affixed to the outer race of the constant velocity universal joint. A rolling
15 diaphragm boot is typically used in this application.

A rolling diaphragm boot is commonly formed of a rubber or silicone
material which is soft enough that a boot of such material is compressible when
crimped into the boot-can connector. However, during the operative life of a
vehicle, the crimping integrity between the rolling diaphragm of the boot formed of
20 soft material and its mating boot-can connector of a constant velocity universal joint
may deteriorate. This may particularly be the case during operation in and exposure
of the constant velocity universal joint to temperature extremes.

Consequently, the need has developed for an improved design for a
constant velocity universal joint which includes an improved rolling diaphragm boot

00303791.043009

and a mating boot-can having an enhanced crimping integrity, and also having improved properties allowing the boot and the crimping integrity to have improved long-term durability and temperature endurance.

Summary Of The Invention

5 It is a principal object according to the present invention to provide an improved constant velocity universal joint having a rolling diaphragm boot and boot-can.

10 It is another object according to the present invention to provide a constant velocity universal joint having a rolling diaphragm boot and boot-can with improved crimping integrity therebetween.

 It is yet another object according to the present invention to provide a rolling diaphragm boot which has improved hot and cold temperature operating performance and durability properties.

15 It is still another object according to the present invention to provide a constant velocity universal joint and propeller shaft assembly according to the present invention which incorporates the improved rolling diaphragm boot design provided herein.

20 It is yet still another object according to the present invention to provide a rolling diaphragm boot of an improved design and material selection to prevent crimping deterioration and slippage of the boot and the crimping integrity between the boot and the boot can.

According to the present invention, therefore, an improved constant velocity universal joint is provided having a boot formed of a thermoplastic elastomer and having a rolling diaphragm shape. The boot has a large diameter crimping lip with material removed therefrom in order to enhance the integrity of the clamping between the boot and the boot-can by reducing the effective stiffness of the boot material.

In carrying out the above objects, features and advantages of the present invention, provided is a boot adapted for coupling to a boot-can connector, the boot being an annular member which has a longitudinal axis and a crimping lip. The crimping lip is received by the boot-can connector and has a plurality of radially distributed apertures which are oriented parallel to the longitudinal axis. The apertures reduce the stiffness and increase the compressibility of the crimping lip. In one preferred embodiment, the plurality of radially distributed apertures of the boot include a plurality of radially distributed holes. And in another preferred embodiment, the plurality of radially distributed apertures of the boot include a plurality of radially distributed cut-outs. For each preferred embodiment, the annular member is preferably formed of a thermoplastic material.

In another embodiment according to the present invention, provided is a boot and boot-can assembly which is adapted for attachment to a housing. The assembly includes a boot-can connector which has a first end for mating with the housing. The boot-can connector also has a second flanged end. Further included is a boot formed of a thermoplastic elastomer material. The boot has an annular lip which is received by the second flanged end of the boot-can connector. The annular lip has a plurality of radially distributed apertures for reducing the stiffness and increasing the compressibility of the annular lip.

In keeping with the present invention, a constant velocity universal joint is provided which has an annular outer race. The constant velocity universal joint includes a boot-can which has a first end for mating with the annular outer race and a second flanged end. The constant velocity universal joint also includes a thermoplastic rolling-diaphragm boot which has an crimping lip which is received by the second end of the boot-can. The crimping lip also includes a plurality of radially distributed apertures which serve to increase the compressibility of the crimping lip.

Further provided in accordance with the present invention is a constant velocity universal joint and propeller shaft assembly. This assembly includes a propeller shaft having a first end. Also included in this assembly is a constant velocity universal joint which receives the first end of the propeller shaft therein. The constant velocity universal joint also has an annular outer race having a first face. Also included is a boot-can which has a large-diameter end and a relatively small-diameter flanged end. The large-diameter end mates with the first face of the outer race. Further included is a thermoplastic boot which has a sealing end, a tubular stem portion for receiving the propeller shaft, and an annular upturned edge which is crimpingly affixed to the relatively small-diameter flanged end of the boot-can. The annular upturned edge has a plurality of radially distributed apertures for increasing the compressibility of the annular upturned edge. The sealing end cooperates with the propeller shaft to provide a seal therewith.

The above objects and other objects, features and advantages of the present invention are readily apparent from the following detailed description of the best mode for carrying out the invention when taken in connection with the accompanying drawings.

Brief Description Of The Drawings

FIGURE 1 is a cross-sectional side view of a constant velocity universal joint and propeller shaft assembly according to the present invention;

FIGURE 2 is a perspective view of a boot and boot-can assembly
5 according to the present invention;

FIGURE 3a is a side view of the boot and boot-can assembly illustrated in Figure 2;

FIGURE 3b is a front view of the boot and boot-can assembly illustrated in Figure 3a;

10 FIGURE 4a is a cross-sectional side view of the boot and boot-can assembly shown in Figure 3a, in an un-crimped state, taken along the line A-A;

FIGURE 4b is an enlarged detail of the encircled portion from Figure 4a, showing the crimping lip of the boot received within the boot can in an un-crimped state;

15 FIGURE 5a is a cross-sectional side view of the boot and boot-can assembly shown in Figure 3a, in a crimped state, taken along the line A-A;

FIGURE 5b is an enlarged detail of the encircled portion from Figure 5a, showing the crimping lip of the boot received within the boot can in a crimped state;

20

The figure consists of nine small diagrams arranged horizontally, each showing a different type of singularity on a curve \$C\$. The labels are as follows:

- (a) A cusp where two branches meet at a single point.
- (b) A node where two branches cross transversely.
- (c) A more complex singularity involving multiple branches meeting at a point.
- (d) A singularity with a loop-like structure.
- (e) A singularity with a sharp corner or kink.
- (f) A singularity with a cusp and a nearby intersection point.
- (g) A singularity with a cusp and a nearby intersection point, similar to (f) but with different branch orientations.
- (h) A singularity with a cusp and a nearby intersection point, showing a different configuration.
- (i) A singularity with a cusp and a nearby intersection point, showing another configuration.

[illegible][illegible]

(a) (b) (c) (d) (e) (f) (g) (h) (i)

[illegible]

Best Mode For Carrying Out The Invention

In accordance with the teachings of the present invention, Figure 1 of the drawings shows a cross-sectional side view of a constant velocity universal joint and propeller shaft assembly 10 according to the present invention. As shown in Figure 1, assembly 10 includes a propeller shaft 12, which in the embodiment illustrated includes a propeller shaft housing tube 14 which has a propeller stub shaft 16 aligned and coupled therewith and projecting therefrom. As is known in the art, the propeller shaft 12 is a drive shaft connecting the transmission (not shown) to the driving axle (or front and rear axles in a four-wheel drive vehicle) in order to transmit torque from the transmission to the axle.

Further included in assembly 10 is a constant velocity universal joint 18, which includes an outer race 20 having outer tracks 22, and an inner race 24 having inner tracks 26. Constant velocity universal joint 18 is of the ball-and-cage variety. Note that constant velocity joint 18 includes a cage 28 which has a plurality of windows therein, each for holding and carrying a corresponding one of a plurality of ball bearings 30. Ball bearings 30 are directed by the cage while riding on the outer and inner tracks 22 and 26, respectively, of joint 18.

Assembly 10 further includes a grease cap 32 therein. Grease cap 32 is mounted to one end of constant velocity universal joint 18 for retaining grease contained within joint 18 for keeping it lubricated and also for keeping any foreign matter and contaminants out of joint 18. As illustrated in Figure 1, grease cap 32 has an annular flange 33 which is secured to a first end 19 of outer race 20. Grease cap 32 may also have a means for venting in order to minimize pressure fluctuations due to expansion and contraction of enclosed air space during operation of the constant velocity universal joint 38. The means for venting is generally a hole in the center dome of grease cap 32. Also illustrated is an adaptor member 34 mounted to the

first end 19 of outer race 20 disposed around grease cap 32. Adaptor member 34 includes a splined bore 36 distal the constant velocity universal joint 18. Splined bore 36 serves to couple propeller shaft 12 and constant velocity universal joint 18 to another vehicle component, such as a transmission or transfer case (not shown).
5 The transmission or transfer case would therefore include a splined shaft which is received within the splined bore 36 of adaptor member 34, so that the transmission or transfer case may provide a power transfer to propeller shaft 12.

In keeping with the present invention, also included in assembly 10 is a boot 38 and a boot-can 40. As shown in the perspective view of Figure 2 and the elevational views of Figures 3a-3b, 4a-4b and 5a-5b, boot 38 and boot-can 40 may form a subassembly 41. As illustrated in Figure 4a, boot 38 is an annular member having a longitudinal axis 42. Boot 38 has a first annular neck member 44 which engages propeller shaft 12 (and more particularly propeller stub shaft 16) in order to provide a seal between constant velocity universal joint 18 and propeller shaft 12, so that (similar to grease cap 32) grease is not able to exit joint 18 and foreign matter and contaminants such as water are not able to enter joint 18 and impede its operation. With reference to Figure 1, first annular neck member 44 of boot 38 is attached to propeller stub shaft 16 with a fastener such as an annular clamp 46 in order to maintain the seal therebetween. Such sealing and protection of
10
15
20
constant velocity universal joint 18 is desired because, once the inner cavity of joint 18 is partially filled with grease and sealed, it is thus lubricated, and preferably lubricated for life with no required maintenance.

Boot 38 is preferably a non-convoluted rolling diaphragm boot. As shown in the cross-section of Figures 1, 4a and 5a, boot 38 transitions from first annular neck member 44 to a stem portion 45, then transitions from stem portion 45 through an outwardly curved (rolling diaphragm) portion 48, which then transitions to a second annular end 50, having a crimping lip 51. Second annular end 50 has a
25

relatively larger diameter than first annular neck member 44. Stem portion 45 is substantially frustoconical in shape and defines a longitudinal opening 47 therethrough for receiving propeller stub shaft 16 therein. As shown in the enlarged views of Figures 4b and 5b, second annular end 50 includes crimping lip 51 having a greater thickness than the other wall portions of boot 38. The rolling diaphragm shape of boot 38 assists in reducing undue forces from being applied to boot 38 at high angular deflection states.

Boot-can 40 provides a means by which boot 38 may be coupled with constant velocity universal joint 18. Boot-can 40 is a connector which allows the relatively small diameter boot 38 to be mounted to the relatively large diameter outer race 20 of constant velocity universal joint 18 (or the second face 21 thereof). As shown in Figures 1-4b, boot-can 40 includes an outer end 52 with an annular flange 53 which is mounted to the second face 21 of outer race 20 of constant velocity universal joint 18 (or the end of outer race 20 which is disposed opposite the end mated to grease cap 32). Boot-can 40 is preferably formed of a metal.

To assist in the mounting of boot-can 40 to outer race 20 universal joint 18, boot-can 40 has a plurality of holes or openings 55 distributed around its outer end 52, which correspond with bores (not shown) in outer race 20 of constant velocity universal joint 18. Accordingly, boot-can 40 may be mechanically fastened to constant velocity universal joint 18, for example, by using bolts 57 (best shown in Figure 1) to fasten the mating components boot-can 40 and outer race 20. The other end 56 of boot-can 40 has a flange 58 which is inwardly turned toward the center of boot-can 40. In order to assemble subassembly 41, boot 38 and boot-can 40 are oriented (as shown in Figures 1-2, 3a-3b, 4a-4b, 5a-5b) so that the second annular portion 50 (and more particularly crimping lip 51) is received by the inwardly turned flange 58 of boot-can 40 (as shown by the "un-crimped" detail of Figures 4a-4b). Subsequently, inwardly turned flange 58 is crimped in order to

secure crimping lip 51 therein, thereby coupling boot 38 and boot-can 40 as shown by the "crimped" detail of Figures 5a-5b.

A preferred embodiment according to the present invention is illustrated in Figures 6a-6c. Shown therein is a boot 38 formed of a thermoplastic elastomer material. Thermoplastic properties provide for a more firm or harder boot than rubber or silicone materials typically utilized in such an application, thus providing additional stability and resistance to environmental contaminants to boot 38. As shown in the first embodiment of boot 38 shown in Figures 6a, 6b and 6c, a plurality of cut-outs 60 are formed in crimping lip 51. Each cut-out 60 is equally radially distributed from axis 42 along the circumference of the crimping lip 51. In a more preferred embodiment, each cut-out 60 is spaced apart in a radially distributed pattern around the circumference of crimping lip 51, as shown in Figure 6b. Thus, boot 38 having the cut-out 60 design for crimping lip 51 has improved properties, including greater compressibility, because the material reduction in crimping lip 51 (due to cut-outs 60) reduces the effective stiffness of the thermoplastic material, thereby allowing the crimping lip 51 to have properties similar to an improved radial spring. Accordingly, the integrity of the crimp seal between crimping lip 51 (of boot 38) and flanged edge 58 (of boot-can 40) is improved, and according to the objectives of the present invention, the crimp integrity improved over the vehicle's life, and also has improved performance in cold temperature operation, where thermoplastic is better able to withstand colder temperatures. Thermoplastic material is also sufficiently rigid and substantial to withstand the loss of material in the crimping lip 51 area, due to cut-outs 60.

In the prior art, thermoplastic elastomer (TPE) materials have not been generally considered for rolling diaphragm boots because of their lower compressibility properties. However a boot made of TPE and having the rolling diaphragm form and one of the crimping lip 51 designs according to the present

invention has greater compressibility properties due to the material reduction, thereby providing for reduced effective stiffness. In this manner, the integrity of the crimp seal is improved.

A second embodiment of a boot 38 according to the present invention is illustrated in Figure 7, and is designated as boot 38'. Note that in the second embodiment disclosed herein, many of the similar components from previous embodiments are designated by like reference numerals carrying prime ('') designations, for consistency and ease of reference. As in the first embodiment of Figures 6a-6c, boot 38' is preferably formed of a thermoplastic material. However, instead of cut-outs 60, an alternative crimping lip 51' design is provided. As shown in Figures 7a, 7b and 7c, crimping lip 51' has formed therein a plurality of relatively small apertures 62 which are formed into crimping lip 51'. Apertures 62 are particularly shown as holes in this embodiment having a diameter smaller than the thickness of crimping lip 51', as shown in Figure 7b. As in the previous embodiment, the apertures 62 are equally radially distributed from the longitudinal axis 42' along the circumference of the crimping lip 51'. More preferably the apertures 62 are spaced apart in a radially distributed pattern around crimping lip 51'. As shown in the side elevational cross-sectional view of Figure 7c (taken along line 7c-7c of Figure 7b), each aperture extends partially into crimping lip 51'.

In one embodiment, the size of cut-outs 60 and apertures 62 are between 35% to 70% of crimping lip 51 thickness. Of course, it is contemplated that cut-outs 60 and apertures 62 may have a size and/or shape as is deemed appropriate and necessary in order to achieve the desired crimping properties according to the objects of the present invention. It is further contemplated that the cut-outs 58 and apertures 60 may be molded or otherwise formed into boots 38, 38', respectively.

Thus the compressed crimping lip 51 thickness ratio is approximately 50% to 70% of the uncompressed crimping lip 51 thickness. The use of the cut-outs 60 or apertures 62 may reduce standard crimping force required by up to approximately 50%. In this manner, the modified geometry has reduced effective stiffness, allowing for a greater degree of compression of the boot-can 40 to boot 30. A thermoplastic elastomer rolling diaphragm boot 38, 38' of this type further includes a better seal integrity over operative its lifetime, and particularly during cold temperature operation.

While the invention has been particularly shown and described in reference to the preferred embodiment thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A boot adapted for coupling to a boot-can connector, the boot comprising:

5

a cylindrical neck member; and

an annular member having a longitudinal axis and a crimping lip for being received by the boot-can connector, said crimping lip having a plurality of radially distributed apertures which are oriented parallel to said longitudinal axis for reducing the stiffness and increasing the compressibility of said crimping lip.

10

2. The boot of claim 1, wherein the plurality of radially distributed apertures are a plurality of equally circumferentially spaced apart holes.

3. The boot of claim 1, wherein the plurality of radially distributed apertures are a plurality of equally circumferentially spaced apart radially distributed cut-outs.

15

4. The boot of claim 1, wherein the annular member is formed of a thermoplastic material.

5. A boot and boot-can assembly adapted for attachment to an outer race of a constant velocity universal joint, the boot and boot-can assembly comprising:

20

a boot-can connector having a first end for mating with the outer race and a second flanged end; and

a boot formed of a thermoplastic material and a having an annular member including a crimping lip for being received by the second flanged end of the boot-can connector, the crimping lip having a plurality of radially distributed

apertures for reducing the stiffness and increasing the compressibility of the crimping lip.

5 6. The boot and boot-can assembly of claim 5, wherein the plurality of radially distributed apertures are a plurality of equally circumferentially spaced apart holes.

7. The boot and boot-can assembly of claim 5, wherein the plurality of radially distributed apertures are a plurality of equally circumferentially spaced apart holes.

10 8. A constant velocity universal joint assembly comprising:
a boot-can having a first end for mating with said outer race and a second flanged end; and
a thermoplastic rolling-diaphragm boot having crimping lip for being received by the second end of the boot-can, the crimping lip having a plurality of radially distributed apertures for increasing the compressibility of the annular lip.

15 9. The constant velocity universal joint assembly of claim 8, wherein the plurality of radially distributed apertures include a plurality of radially distributed holes.

20 10. The constant velocity universal joint assembly of claim 8, wherein the plurality of radially distributed apertures include a plurality of radially distributed cut-outs.

11. A constant velocity universal joint and propeller shaft assembly comprising:
a propeller shaft having a first end;

5

10

12. The constant velocity universal joint and propeller shaft assembly of claim 11, wherein the plurality of radially distributed apertures include a plurality of radially distributed holes.


15

13. The constant velocity universal joint and propeller shaft assembly of claim 11, wherein the plurality of radially distributed apertures include a plurality of radially distributed cut-outs.

Abstract

5 A rolling diaphragm boot is adapted for coupling to a boot-can connector. The boot includes an annular member having a longitudinal axis and a crimping lip for being received by the boot-can connector. The crimping lip has a plurality of radially distributed apertures which are oriented parallel to the longitudinal axis for reducing the stiffness and increasing the compressibility of the crimping lip.

00000000.000000






FIGURE 2




FIGURE 3b




FIGURE 3a




FIGURE 4a




FIGURE 4b




FIGURE 5a




FIGURE 5b





FIGURE 6b




FIGURE 6c




FIGURE 7a




FIGURE 7b




FIGURE 7c

09303791.0430099

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original and first inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled A BOOT FOR A CONSTANT VELOCITY UNIVERSAL JOINT specification of which was filed herewith;

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s): Priority Claimed

(Number)	(Country)	YES	NO	(Day/Month/Year Filed)
(Number)	(Country)	YES	NO	(Day/Month/Year Filed)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status - patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status - patented, pending, abandoned)

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Mick A. Nylander (Registration No. 37,200)

Address all correspondence and telephone calls to Mick A. Nylander, at GKN Automotive, Inc., 3300 University Drive, Auburn Hills, Michigan 48326-2362.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Rory Matthew Johnson

Inventor's signature Rory Matthew Johnson Date 30-APR-99

Post Office Address 152 Fox Chase Boulevard, Grand Blanc, Michigan 48439 Citizenship U.S.A.

Residence same as above

Full name of second joint inventor _____

Inventor's signature _____ Date _____

Post Office Address _____ Citizenship _____

Residence same as above